

HAKKO FR-300

New Handy and Portable Desoldering tool



[Features]

- **Easy handling**
 - ・ Well balanced
 - ・ Main switch and temperature volume built in the handle
- **Excellent heat recovery for lead free application with closed-loop heat control**
- **Single touch nozzle replacement**

[Specifications]

Power consumption	95W (Heater 80W)
Temperature range	350-500℃
Standard nozzle	Ø1.0mm (N50-04)
Nozzle to ground resistance	< 2Ω
Nozzle to ground potential	< 2mmV
Vacuum pump	Diaphragm pump
Vacuum pressure	610mmHg
Cord length	1.8m
Dimensions (w/o cord)	210(W)x192(H)x47(D)mm

[Nozzle] *

N50-01	S-Nozzle 0.8mm
N50-02	S-Nozzle 1.0mm
N50-03	Nozzle 0.8mm
N50-04	Nozzle 1.0mm
N50-05	Nozzle 1.3mm
N50-06	Nozzle 1.6mm

*New nozzle can be used for the current desoldering tool, which accepts A1002-A1007.

*Standard pack quantity for the nozzle is 10pcs

HAKKO CORPORATION

Head Office : 4-5, Shiokusa 2-chome, Naniwa-ku, Osaka 556-0024 Phone : +81(0)6 6561-3225 Fax : +81 (0)6 6561-8466