



REF: 010068N0000

✓ CE (EMC), □ UL, □ CE (LVD)

## MY68N

ACCURATE DMM WITH 2000A MEAS

- 3 3/4 digits LCD, max. reading 3999
- Auto/manual ranging, auto power off
- Data hold for easy reading
- Measures 400AAC/DC current using external transducer (optional)
- Overload protection
- Safety as per IEC1010-1 Cat.II 1000V

### Technical specifications

DCV: 400m/4/40/400/1000V,  $\pm 0.7\%$

ACV: 400m/4/40/400/750V,  $\pm 0.8\%$

DCA: 400 $\mu$ /4m/40m/400m/10A,  $\pm 1.2\%$   
40/400A (clamp, 0.1mV/0.1A),  $\pm 1.0\%$

ACA: 400 $\mu$ /4m/40m/400m/10A,  $\pm 1.5\%$   
40/400A (clamp, 0.1mV/0.1A),  $\pm 1.0\%$

OHM: 400/4k/40k/400k/4M/40M  $\Omega$ ,  $\pm 1.2\%$

CAP: 4n/40n/400n/4  $\mu$ /40  $\mu$ /200  $\mu$  F,  $\pm 3.0\%$

FREQ: 100/1k/10k/200kHz,  $\pm 2.0\%$

Duty cycle: 0.1~99%

Audible continuity & diode test

Transistor  $h_{FE}$ : 0~1000

Dimensions & weight: 91x189x31.5mm, ~310g

Battery: 9Vx1, 6F22

Accessories: holster

**Sinometer**